

# Residential LIVING. Waterproof Carpet Cushion



SPECIFICATION	Blue Residential Waterproof Carpet Cushion	Green Residential Waterproof Carpet Cushion	Test Standard
Recommended Use:	Residential	Residential	N/A
Item Number:	2200000389	2200000388	N/A
Composition:	Foam	Foam	N/A
Thickness:	5/16 in (8 mm)	7/16 in (11 mm)	ASTM D3574
Density:	3.0 lbs/ft3	3.0 lbs/ft3	ASTM D3574
R-Value:	1.194	1.810	ASTM C518
Color:	Blue	Green	N/A
Roll Size:	50 yd²	40 yd²	N/A
Dimension:	6 ft x 75 ft	6 ft x 60 ft	N/A

### **PERFORMANCE**

Liquid Penetration by Spillage:	Passed	Passed	AATCC 205 Carpet
CDF psi@ 25% & 65%:	201.8 lbs & 1,136.1 lbs	183.4 lbs & 1,070.4 lbs	ASTM D3574
Compression Set at 50%:	17.0%	21.7%	ASTM D3574
Resistance of Fungal Growth:	Passed	Passed	ATM G21

#### **ACOUSTICAL PROPERTIES**

Sound Transmission Class (STC):	60	59	ASTM E413
Impact Insulation Class (IIC):	93	92	ASTM E989
High-Frequency Impact Insulation Class (HIIC):	97	96	ASTM E3222

## **FLAMMABILITY**

Federal Flammability Standard	Passed	Passed	ASTM D2859
CPSC FF 1-70:			

# **PROTECTION**

Antimicrobial	Passed	Passed	N/A
Warranty	Lifetime	Lifetime	N/A



